

iSeed®

Settings for Vredo Sport series



Guidelines & remarks

- Bottom valve: 1 (= closed)
- Seed rate 1-10 for bare seed and 1-8 for iSeed®.
- Fill hopper in field in order to avoid compaction.
- Do not completely fill the hopper in order to avoid too much pressure on the seed rudder
- Avoid the older Vredo-types that have brushes at the bottom of the hopper.



Calibrations for Vredo Sport series

BARE SEED	
MACHINE SHAFT SETTING	KG/HA
1	6,6
2	15,4
3	27,4
4	41,6
5	55,6
6	69,0
7	88,8
8	108,4
9	130,2
10	156,4

ISEED®	
MACHINE SHAFT SETTING	KG/HA
1	8,6
2	19,8
3	36,8
4	58,2
5	81,2
6	99,2
7	134,0
8	166,6
9	199,4
10	251,4

ISEED® / BARE SEED	
MACHINE SHAFT SETTING	RATIO
1	1,30
2	1,29
3	1,34
4	1,40
5	1,46
6	1,44
7	1,51
8	1,54
9	1,53
10	1,61



DLF-TRIFOLIUM

Ny Østergade 9 - DK 4000 Roskilde
 Tel. +45 46 33 03 00 - Fax +45 46 32 08 30
www.dlf.com - dlf@dlf.com

The above calibration is an example. Always make your own calibrations before sowing!